


ACCUTHREAD

ATH-8, ATH-12, ATH-16

Single End Threading Module



Threading Module available on 8, 12 and 16mm capacity unit utilizing roll-thread head and standard roll-thread inserts



MODULAR



ACCUTHREAD Single End Threading Module

ATH-8, ATH-12, ATH-16

Model	Power	WireRange	Size	Weight	Maximum Spindle Speed
ATH-8	6 KVA	.080 to .315 (2mm to 8mm)	40" X 52" X 60"	2300 lbs (1044 kg)	3000 RPM
ATH-12	8 KVA	.157 to .472 (4mm to 12mm)	44" X 52" X 60"	2400 lbs (1090 kg)	3000 RPM
ATH-16	11 KVA	.250 to .625 (6mm to 16mm)	54" X 52" X 66"	3050 lbs (1385 kg)	3000 RPM

FEATURES


- 3 Head unit, capable of chamfering, turning down, and roll threading
- Quick tool changeover
- Industry standard threading heads, chamfer tools, and turning heads
- Threading inserts for English and Metric materials
- Pneumatic clamp on ATH-8 and ATH-12
- Hydraulic clamp on ATH-16
- Threading up to 4" (100mm) of wire (depends on wire diameter)

BENEFITS

- Reduce production costs by eliminating additional parts handling
- Increases machine capabilities to do more complex parts complete, without the need for manual secondary operations
- Greater ability to quote/bid more complex geometries, resulting in a competitive advantage

One threading tool set included per customer specification

Available on AFM modular machine systems



Automated Industrial Machinery, Inc. ©2024.
The Manufacturer Reserves the right to alter any data and/or photos provided in this brochure without notice.

FORMING OUR FUTURE WITH YOURS

WWW.AIMMACHINES.COM

AIM, Inc.
14103 McCormick Drive,
Tampa, FL 33626 U.S.A.
Tel: +1 813.818.8222
sales@aimmachines.com

For online videos visit:
www.youtube.com/wirebenders

