ACCUTHREAD ATH-8, ATH-12, ATH-16







Threading Module available on 8, 12 and 16mm capacity unit utilizing roll-thread head and standard roll-thread inserts





ACCUTHREAD Single End Threading Module

ATH-8, ATH-12, ATH-16

Model	Power	Wire Range	Size	Weight	Maximum Spindle Speed
ATH-8	6 KVA	.080 to .315 (2mm to 8mm)	40" X 52" X 60"	2300 lbs (1044 kg)	3000 RPM
ATH-12	8 KVA	.157 to .472 (4mm to 12mm)	44" X 52" X 60"	2400 lbs (1090 kg)	3000 RPM
ATH-16	11 KVA	.250 to .625 (6mm to 16mm)	54" X 52" X 66"	3050 lbs (1385 kg)	3000 RPM

FEATURES

3 Head unit, capable of chamfering, turning down, and roll threading Quick tool changeover Industry standard threading heads, chamfer tools, and turning heads Threading inserts for English and Metric materials Pneumatic clamp on ATH-8 and ATH-12 Hydraulic clamp on ATH-16

Threading up to 4" (100mm) of wire (depends on wire diameter)

BENEFITS

Reduce production costs by eliminating additional parts handling Increases machine capabilities to do more complex parts complete, without the need for manual secondary operations Greater ability to quote/bid more complex geometries, resulting in a competitive advantage

One threading tool set included per customer specification

Available on AFM modular machine systems







AIM Europe S.A.
68th Km N. Rd Athens-Lamia
Paleohori, P.O. Box 36
32 009, Greece
Tel: +30 22620.58900
Fox: +30 22620.59231
info@AIMEurope\$A.com



